



NOTES, UNLESS OTHERWISE SPECIFIED:

1. MATERIAL:
 - 1.1 CAGE: 301 CRES PER MIL-S-5059.
 - 1.2 SCREW: A286 CRES PER AMS5731, AMS5737.
 - 1.3 HOUSING: 300 SERIES CRES PER ASTM-A-581/582, AMS5640, QQ-S-763.
2. HEAT TREAT:
 - 2.1 SCREW: 140 KSI MINIMUM PER AMS-H-6875.
- 3.1 FINISH:
 - 3.1 HOUSING: PASSIVATE PER AMS-QQ-P-35.
 - 3.2 SCREW: ELECTROFILM #2006.
 - 3.3 CAGE: PASSIVATE PER AMS-QQ-P-35 OR CADMIUM PLATE PER QQ-P-416 TYPE II, CLASS 2.
4. FLOAT: .020 RADIALLY FROM CENTER.
5. PART NUMBER CALLOUT:
 - 5.1 CA2044 DENOTES ASSEMBLY WITH PASSIVATED CAGE.
 - 5.2 CA2044C DENOTES ASSEMBLY WITH CADMIUM PLATED CAGE.
6. FOR USE WITH ANY CA2000 SERIES STUD ONLY.
7. WEIGHT: .0053 LBS./EA.
8. TOLERANCE; UNLESS OTHERWISE SPECIFIED:
DECIMALS, .XX = .02, .XXX = .010, ANGLE, = ±2°.

APPROVED DATE	FAIRCHILD FASTENERS ENGINEERING CENTER 3000 WEST LOMITA BOULEVARD TORRANCE, CA 90505	CAGE CODE 29372		
14 NOV 73		TRIDAIR PRODUCT		
REV. LETTER AND DATE		ASSEMBLY FLOATING RECEPTACLE	CA2044()	
E 4 AUG 99				SHEET 1 OF 1
DAF NUMBER				
DAF 45128				