


| .190-32 SIZE FIRST DASH NO.-10 | G GRIP | | | | | | | | | L LENGTH |
|--------------------------------|--------|-------|-------|-------|-------|-------|-------|--------|-------|----------|
| | .062 | .094 | .125 | .156 | .187 | .218 | .250 | .281 | .312 | |
| -2-9 | -3-9 | -4-9 | -5-9 | -6-9 | -7-9 | -8-9 | -9-9 | -10-9 | .562 | |
| -2-10 | -3-10 | -4-10 | -5-10 | -6-10 | -7-10 | -8-10 | -9-10 | -10-10 | .625 | |
| -2-11 | -3-11 | -4-11 | -5-11 | -6-11 | -7-11 | -8-11 | -9-11 | -10-11 | .687 | |
| -2-12 | -3-12 | -4-12 | -5-12 | -6-12 | -7-12 | -8-12 | -9-12 | -10-12 | .750 | |
| -2-13 | -3-13 | -4-13 | -5-13 | -6-13 | -7-13 | -8-13 | -9-13 | -10-13 | .812 | |
| -2-14 | -3-14 | -4-14 | -5-14 | -6-14 | -7-14 | -8-14 | -9-14 | -10-14 | .875 | |
| -2-15 | -3-15 | -4-15 | -5-15 | -6-15 | -7-15 | -8-15 | -9-15 | -10-15 | .937 | |
| -2-16 | -3-16 | -4-16 | -5-16 | -6-16 | -7-16 | -8-16 | -9-16 | -10-16 | 1.000 | |
| -2-17 | -3-17 | -4-17 | -5-17 | -6-17 | -7-17 | -8-17 | -9-17 | -10-17 | 1.062 | |
| -2-18 | -3-18 | -4-18 | -5-18 | -6-18 | -7-18 | -8-18 | -9-18 | -10-18 | 1.125 | |
| -2-19 | -3-19 | -4-19 | -5-19 | -6-19 | -7-19 | -8-19 | -9-19 | -10-19 | 1.187 | |
| -2-20 | -3-20 | -4-20 | -5-20 | -6-20 | -7-20 | -8-20 | -9-20 | -10-20 | 1.250 | |
| -2-21 | -3-21 | -4-21 | -5-21 | -6-21 | -7-21 | -8-21 | -9-21 | -10-21 | 1.312 | |
| -2-22 | -3-22 | -4-22 | -5-22 | -6-22 | -7-22 | -8-22 | -9-22 | -10-22 | 1.375 | |
| -2-23 | -3-23 | -4-23 | -5-23 | -6-23 | -7-23 | -8-23 | -9-23 | -10-23 | 1.437 | |
| -2-24 | -3-24 | -4-24 | -5-24 | -6-24 | -7-24 | -8-24 | -9-24 | -10-24 | 1.500 | |
| -2-25 | -3-25 | -4-25 | -5-25 | -6-25 | -7-25 | -8-25 | -9-25 | -10-25 | 1.562 | |
| -2-26 | -3-26 | -4-26 | -5-26 | -6-26 | -7-26 | -8-26 | -9-26 | -10-26 | 1.625 | |
| -2-27 | -3-27 | -4-27 | -5-27 | -6-27 | -7-27 | -8-27 | -9-27 | -10-27 | 1.687 | |
| -2-28 | -3-28 | -4-28 | -5-28 | -6-28 | -7-28 | -8-28 | -9-28 | -10-28 | 1.750 | |

NOTES:

- MATERIAL: A286 CRES PER AMS5731, AMS5737.
- HEAT TREAT: 140,000 PSI MIN. TENSILE PER AMS5737.
- FINISH: PASSIVATE PER QQ-P-35.
- MINIMUM ULTIMATE TENSILE STRENGTH (CALCULATED): 2420 LBS.
- MINIMUM ULTIMATE SINGLE SHEAR STRENGTH (CALCULATED): 1970 LBS.
- SCREW TO BE USE WITH CA2210-10R RETAINING RING TO CAPTIVE TO PANEL.
- PANEL PREPARATION: REFER TO CAL-STD-0260.
- INSTALLATION: REFER TO TRIDAIR DRAWING CA2210T-()

.10 PART CALLOUT EXAMPLE: CA2217-10-4-20



| INTERIM DOCUMENT REVISION | | Rev. | Date | DAF # |
|---------------------------|--|------|---------|-------|
| | | A1 | 4/21/16 | 94301 |

DRAWING PROVIDES FORM, FIT AND FUNCTION DATA. DO NOT ATTEMPT TO MANUFACTURE PRODUCT USING THIS DRAWING.

| | | |
|----------------------------|-----------------|--------|
| DRAWN BY: J. STAFFORD | DATE 4-19-90 | TITLE: |
| MFG. ENGRG: | DATE | |
| APPROVED BY: <i>Jmf</i> | DATE 4-19-90 | |
| APPROVED BY: | DATE | |
| PROJECT NUMBER: S42722 | 90-141 | |

| | | |
|--|---------------------------------|-----------------------------------|
| SCREW, CAPTIVE, HEX HEAD, CRES, #10-32 SIZE | | |
| UNLESS OTHERWISE SPECIFIED: TOLERANCES: DECIMALS: .XX ± .02 .XXX ± .010 ANGLES: ± 2° | MILLIMETERS ± 0.50 ± 0.25 | SURFACE FINISH 125 MICROINCHES |

| | | |
|--------------------------|-------|--|
| Tridair | | Reznard SFD 3000 W. Lomita Blvd Torrance, CA 90505 213/530-2220 |
| CA2217-10-1 J-1 J | | |
| FSC:29372 | SHEET | 1 OF 1 |

150-26035-11-19-91

REVISION

SCANNED